

Specifications



Certificate No. FM 29157

CAPACITIES						
MODEL	1410	1413	1513	1515	1615	1623
Feed opening, mm	1100x900	1300x900	1300x1000	1500x1000	1500x1300	2300x1300
Primary Capacity tonnes per hr. Nominal 75mm product	200	350	500	600	650	1000
Primary Max. Feed Size (edge length) mm	600	700	900	900	1000	1000
Secondary Capacity tonnes per hr. Nominal 40mm product	180	280	350	430	520	700
Secondary Max. Feed Size (edge length) mm	300	350	450	450	500	500

APPROXIMATE DIMENSIONS AND POWERS						
MODEL	1410	1413	1513	1515	1615	1623
Primary Installed Power (Max.) kW	200	350	500	600	650	1000
Secondary Installed Power (Max.) kW	132	185	225	280	315	500
Length, metres	2.6	3.5	3.9	3.9	4.25	4.25
Width, metres	2.6	3.3	3.3	3.5	3.8	4.5
Height, metres	2.2	2.8	3.6	3.6	3.5	3.5

APPROXIMATE SHIPPING SPECIFICATION No case – local protection only.						
MODEL	1410	1413	1513	1515	1615	1623
Net Weight, Kg	18,150	26,000	34,500	37,100	54,000	65,000
Rotor Weight, Kg	5,500	8,000	10,000	12,000	18,000	26,000

The above information is for guidance purposes only. Capacities refer to typical limestone applications. Actual throughput and power requirement will vary according to characteristics of material and product sizing.

For more details, contact your nearest Jeffrey office.



EUROPE
British Jeffrey Diamond
Division of INDRESCO UK Ltd.
Thornes Moor Road,
Wakefield
West Yorkshire WF2 8PT
England
Telephone: 01924 201740
Fax: 01924 361740

U.S.A.
Jeffrey Division
P.O. Box 387
Woodruff
SC 29388
U.S.A.
Telephone: 803/476-7523
Fax: 803/476-7523

AUSTRALIA
Jeffrey Division
INDRESCO Pty. Ltd.
Karoonda Close, Rathmines
Mail: P.O. Box 282
Toronto, N.S.W. 2283
Australia
Telephone: 049 75-2888
Fax: 049 75-2683

SOUTH AFRICA
KOMDRESCO
Tedstone Road
Mail: P.O. Box 14043
Wadeville 1422
Transvaal, South Africa
Telephone: 011 827-1521
Fax: 011 827-2304